

O-ring Mechanical Series

... HMRO-A

● Operational Conditions:

Temperature: -20℃ to +150℃

Pressure: ≤1.0MPa

Speed: ≤15m/s

● Materials:

Stationary Ring: B


Rotary Ring: F,U2

Secondary Seal: P,E,V,T

Spring and Metal Parts: F,G

● Seat Types:

● Applications: Clean water, sewage water, oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	d	D3	D2	D1	L7	L1	L2	L3
20	20	34	36	42	18	35	23	25
22	22	36	38	44	18	35	23	25
24	24	38	40	46	18	35	23	25
25	25	39	41	47	18	35	23	25
28	28	42	44	50	18	35	23	25
30	30	44	46	52	18	35	23	25
32	32	46	48	54	18	35	23	25
33	33	47	49	55	18	35	23	25
35	35	49	51	57	18	35	23	25
38	38	54	56	64	20	38	25	27
40	40	56	60	66	20	38	25	27
42	42	58	62	68	20	38	25	27
43	43	59	63	69	20	38	25	27
45	45	61	65	71	20	38	25	27
48	48	64	68	74	20	38	25	27
50	50	66	70	76	20	39	25	27
52	52	68	72	78	20	40	25	27
53	53	69	73	79	20	40	25	27
55	55	71	75	81	20	40	25	27
58	58	76	83	89	22	41	28	30
60	60	78	85	91	22	41	28	30
62	62	80	87	93	22	41	28	30
63	63	81	88	94	22	41	28	30
65	65	83	90	96	22	41	28	30
68	68	86	93	99	24	41	30	32
70	70	90	95	101	24	42	30	32
75	75	95	104	110	24	42	30	32
80	80	100	109	115	25	42	31	33
85	85	105	114	120	25	43	31	33
90	90	110	119	125	25	45	31	33
95	95	115	124	130	25	45	31	33