

O-ring Mechanical Series

... HM40

● Operational Conditions:

Temperature: -20℃ to +180℃

Pressure: ≤ 2.5MPa

Speed: ≤ 15m/s

● Materials:

Stationary Ring: Q1, Q2, U2

Rotary Ring: B, A, Q1, Q2, U2

Secondary Seal: P, E, V


Spring and Metal Parts: F, G, M

● Seat Types:

Standard: GW24DINL

Alternative: GWT21

● Applications: Clean water, sewage water, oil and other moderately corrosive fluids



规格/Size (公制/Metric)	规格/Size (英制/Inch)	D3	D1	L	L1	L2
18		32.5	33	40.0	30.0	10.0
19	0.750	33.5	35	40.0	30.0	10.0
20		34.5	35	40.0	30.0	10.0
22	0.875	36.5	37	40.0	30.0	10.0
24		38.5	39	40.0	30.0	10.0
25		39.5	40	40.0	30.0	10.0
	1.000	39.5	43	40.0	30.0	10.0
28		42.5	43	42.5	32.5	10.0
	1.125	42.5	45	42.5	32.5	10.0
30		44.5	45	42.5	32.5	10.0
32	1.250	46.0	48	42.5	32.5	10.0
33		47.0	48	42.5	32.5	10.0
35	1.375	48.0	50	42.5	32.5	10.0
38	1.500	52.0	56	45.0	34.0	11.0
40		56.0	58	45.0	34.0	11.0
42	1.625	58.0	61	45.0	34.0	11.0
43		59.0	61	45.0	34.0	11.0
44-45	1.750	59.0	63	45.0	34.0	11.0
48	1.875	62.4	66	45.0	34.0	11.0
50	2.000	65.6	70	47.5	34.0	13.0
53	2.125	68.8	73	47.5	34.5	13.0
55		70.8	75	47.5	34.5	13.0
	2.250	71.9	78	47.5	34.5	13.0
58		75.2	78	47.5	34.5	13.0
60	2.375	75.2	80	47.5	34.5	13.0
63		78.3	83	47.5	34.5	13.0
	2.500	78.3	85	47.5	34.5	13.0
65		84.2	85	49.0	36.5	13.0
68	2.625	85.5	90	51.3	36.5	15.3
70	2.750	87.4	92	51.3	36.5	15.3
73	2.875	90.6	97	51.3	36.5	15.3
75		92.7	97	51.3	36.5	15.3
	3.000	93.7	105	51.7	36.5	15.7
80	3.125	100.0	105	51.7	36.5	15.7
	3.250	100.0	110	51.7	36.5	15.7
85	3.375	103.3	110	51.7	36.5	15.7