

### ● Operational Conditions:

Temperature: -40 °C to +150 °C

Pressure: ≤ 1.0 MPa

Speed: ≤ 15 m/s

### ● Materials:



Stationary Ring: Q235, V1

Rotary Ring: Q235, U2

Secondary Seal: P, E, V

Spring and Metal Parts: F, G

### ● Applications: Clean water, sewage water, Oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	D1	D2	D3	L1	L11	L12	L2
10	21.0	17.0	20.0	13.4	25.9	33.4	6.6
12	23.0	19.0	22.0	14.4	25.9	33.4	6.6
14	25.0	21.0	24.0	14.4	28.4	33.4	6.6
15	27.0	23.0	25.0	14.4	28.4	33.4	6.6
16	27.0	23.0	26.0	14.4	28.4	33.4	6.6
18	33.0	27.0	32.0	18.5	30.0	37.5	7.5
20	35.0	29.0	34.0	18.5	30.0	37.5	7.5
22	37.0	31.0	36.0	18.5	30.0	37.5	7.5
24	39.0	33.0	38.0	18.5	32.5	42.5	7.5
25	40.0	34.0	39.0	18.5	32.5	42.5	7.5
28	43.0	37.0	42.0	24.5	35.0	42.5	7.5
30	45.0	39.0	44.0	25.5	35.0	42.5	7.5
32	48.0	42.0	46.0	25.5	35.0	47.5	7.5
33	48.0	42.0	47.0	25.5	35.0	47.5	7.5
35	50.0	44.0	49.0	26.5	35.0	47.5	7.5
38	56.0	49.0	54.0	29.0	36.0	46.0	9.0
40	58.0	51.0	56.0	29.0	36.0	46.0	9.0
43	61.0	54.0	59.0	29.0	36.0	51.0	9.0
45	63.0	56.0	61.0	29.0	36.0	51.0	9.0
48	66.0	59.0	64.0	31.0	36.0	51.0	9.0
50	70.0	62.0	66.0	30.5	38.0	50.5	9.5
53	73.0	65.0	69.0	29.0	36.5	59.0	11.0
55	75.0	67.0	71.0	29.0	36.5	59.5	11.0
58	78.0	70.0	78.0	32.0	41.5	59.5	11.0
60	80.0	72.0	80.0	34.0	41.5	59.5	11.0
65	85.0	77.0	85.0	34.0	41.5	69.0	11.0
68	90.0	81.0	88.0	33.7	41.2	68.7	11.3
70	92.0	83.0	90.0	33.7	48.7	68.7	11.3
75	97.0	88.0	99.0	40.7	48.7	68.7	11.3
80	105.0	95.0	104.0	40.5	48.0	78.0	12.0
85	110.0	100.0	109.0	38.5	46.0	76.0	14.0
90	115.0	105.0	114.0	38.5	51.0	76.0	14.0
95	120.0	110.0	119.0	38.5	51.0	76.0	14.0
100	125.0	115.0	124.0	38.5	51.0	76.0	14.0