
HM108





型号MODEL	DI	D3	D7	L	L3	LA
HM108-9	9	20.0	21	20	15.0	5.0
HM108-10	10	20.0	21	20	15.0	5.0
HM108-11	11	22.0	23	20	15.0	5.0
HM108-12	12	22.0	23	20	15.0	5.0
HM108-14	14	24.5	25	25	20.0	5.0
HM108-15	15	26.5	27	25	20.0	5.0
HM108-16	16	26.5	27	25	20.0	5.0
HM108-17	17	32.0	33	25	20.0	5.0
HM108-18	18	32.0	33	25	20.0	5.0
HM108-19	19	34.0	35	25	20.0	5.0
HM108-20	20	34.0	35	25	20.0	5.0
HM108-22	22	37.0	37	28	22.0	6.0
HM108-25	25	39.0	40	32	24.0	8.0
HM108-28	28	42.0	43	35	27.0	8.0
HM108-30	30	45.0	45	35	27.0	8.0
HM108-35	35	50.5	50	37	29.0	8.0
HM108-40	40	57.5	58	40	31.5	8.5
HM108-45	45	62.5	63	40	31.5	8.5

Applications

- ► Temperature:-20~+100°C
- ▶ Pressure:≤0.5MPa
- ▶ Speeds: ≤5m/second
- Medium:User in the water pumps and agitator pumps.