


HMCS-B01(H10/H8)


Type: Multi Spring Cartridge Seal
Replacement: Burgmann H10/H8
Temperature: -20°C to +250°C
Pressure : ≤ 2.5 Mpa Speed :
Material: ≤ 35 m/s
A,Q1,Q2,U2,P,E,V,F,G



H8



H10



d (mm)	D1	D2	D4	D5	D6	L +/-0.5	L1
15	16	42	22.6	21	34	17	15.0
18	19	45	25.6	24	37	17	15.0
20	21	48	27.6	26	40	17	15.0
22	23	50	29.6	28	42	17	15.0
25	26	52	32.8	31	44	17	15.0
28	29	55	35.8	34	47	17	15.0
30	31	58	37.8	36	50	17	15.0
32	33	60	39.8	38	52	17	15.0
35	36	62	42.8	41	54	17	15.0
38	39	65	45.9	44	57	17	15.0
40	41	68	47.9	46	60	17	15.0
42	43	72	49.9	48	64	17	15.0
45	46	75	52.9	51	67	17	15.0
48	49	80	55.9	54	72	17	15.0
50	51	80	58.2	56	72	17	15.0
52	53	82	60.2	58	74	17	15.0
55	56	85	63.2	61	77	17	15.0
58	59	9	66.7	64	82	17	15.0
60	61	90	68.7	66	82	17	15.0
65	66	95	73.7	71	87	19	16.5
68	69	100	76.7	74	92	19	16.5
70	71	100	78.7	76	92	19	16.5
75	76	108	83.7	81	100	19	16.5
80	81	112	88.7	86	104	19	16.5
85	86	118	93.7	91	110	19	16.5
90	91	122	99.5	96	114	19	16.5
95	96	128	104.5	101	120	19	16.5
100	101	132	109.5	106	124	19	16.5